



MILOSH 2

Multirole armoured tactical vehicle 4x4



TECHNICAL DATA:

- Type
- Drive mode
- Length, overal (incl. winch)
- Width (excl. side rear view mirrors)
- Height, to the roof panel (load 18 t)
- · Height, incl. 20/3 mm RCWS
- Interaxle spacing
- Wheelbase
- · Weight, empty vehicle
- · Max. weight
- · Number of seats
- · Ballistic protection
- · Anti-mine protection

Armored wheeled vehicle, with 4 side doors, hydraulic ramp on the rear, with door incorporated, and 2 roof hatches.

4x4 (non-switchable)

6.5 m

2.61 m

cc. 2.38 m

cc. 3.25 m

3.7 m

2.14 m

cc. 15.5 t

18 t

10

Level BR6 as per GOST R507 44-95 (from 12.7 mm x 108 PPZ), Level 3 as per STANAG 4569 (from 7.62 mm x 54 PPZ and 7.62 mm x 51 WC) Level 2a and 2b as per STANAG 4569 (from 6kg of TNT)

Exploitation Characteristics

Front approach angle	45°
Rear approach angle	40°
Fording capacity	
(when approaching at right angle)	0.8 m
Vertical obstacle (escarpment),	
overcome with both wheels at the same time	0.5 m
Slope	60%
Side slope	30%
Trench	0.9 m
Clearance	0.41 m
	Rear approach angle Fording capacity (when approaching at right angle) Vertical obstacle (escarpment), overcome with both wheels at the same time Slope Side slope Trench

ClearanceTurn radius, minimum

(measuring the outside wheel track)
Speed, maximum
Speed, at intersected terrain, slope 6-8%
Autonomy
8 m
100 km/h
30 km/h
600 km

• Fuel consumption on hard surface roads 30-35 l/100 km



2140 2610

3700

6500

Engine

• Type 4-stroke diesel, water cooled,

with turbocharger, intercooler and ECM unit

• Displacement 6.7 l

• Power at 2800 rpm⁻¹ 221 kW (300 HP)

Max. torque at 1400-1700 rpm-¹ 1100 Nm
 Fuel type diesel
 Fuel tank, volume 290 l

Transmission

Type Automatic, with retarder

Transfer Case

• Type Mechanical, 2 step transfer case, with neutral gear, differential, and parking brake.

Wheels

• Tyre, maximum carrying capacity 4.5 t

 RUN-FLAT mileage (distance covered in a continuous operation even with a damaged tyre)

on hard surface roads 50 km at the speed of 50 km/h (on an asphalt road)

Vehicle Video System

• Camera type Day camera (night vision camera when combined with IR lamp)

• Camera, total number 4 (1 front camera, 2 side ones, and 1 rear one)

Types of armament

- RCWS 20/3 mm KERBER
- RCWS 20 mm



