

## NDS X3 Day time scope



NDS X3 is military grade x3 magnification prismatic day time scope. Due to the exceptional field of view it can be used for surveillance, monitoring and sighting during the day. Also, a large field of view makes it perfect for pairing with night cameras and thermal clip-on systems.

Compact lightweight design. Easily and quickly mounted on the Picatinny rail. In addition sight NDS X3 on the upper side may have a Picatinny rail for small reflex sights, such as RN x1 or other accessory.

Supplied with flip-up cover for ocular and objective in soft carrying case. With day time scope is provided and cleaning tissue.

| <ul> <li>Magnification</li> </ul>         | x3 ±5%         |
|---|----------------|
| <ul> <li>Filed of view</li> </ul>         | ≥ 6°           |
| <ul> <li>Diopter adjustment</li> </ul>    | ±2 Dptr        |
| <ul> <li>Objective</li> </ul>             | 32 mm          |
| <ul> <li>Exit pupil</li> </ul>            | 8,7 mm         |
| • Eye reliefe                             | 72 mm          |
| <ul> <li>Reticule adjustment</li> </ul>   | ±0-43          |
| One click on 100m distance                | e ±0-14        |
| <ul> <li>Input voltage</li> </ul>         | 3 VDC          |
| <ul> <li>Battery type</li> </ul>          | CR2032         |
| <ul> <li>Battery life</li> </ul>          | 200 hours      |
| • Weight                                  | 0,471 kg       |
| <ul> <li>Lenght/Width/Height</li> </ul>   | 149x80x59,5 mm |
| <ul> <li>Operating temperature</li> </ul> | -30°C to +55°C |
| <ul> <li>Storage temperature</li> </ul>   | -35°C to +65°C |
| Immersion                                 | 30 min for 1 m |





Should you have any further enquires, please do not hesitate to contact us at office@yugoimport.com All the data given in the brochure are for information purposes only. The final configuration and/or technical specification are defined for each contract individually.