

# 7.62 x 39 mm, BALL M43

# Rifle ammunition

Full metal jacket bullet, steel+ lead/antimony alloy core. For military applications, training and target shooting. UN transport classification UN 0012. Hazard Division 1.45.

#### **Dimensions and weight:**

Round length, maximum (mm)
Bullet length, maximum (mm)
Case length, maximum (mm)
Round weight (g)

• Round weight (g) approx. 17.0 • Bullet weight (g)  $7.97 \pm 0.10$ 

### **Powder charge:**

Type: spherical double base propellant

• Weight (g): 1.50-1.70

≤35

3

#### Characteristics (Meet General Specification for PdD SAWS Small Caliber Ammunition requirements):

Velocity at 24m, 21±2°C, standard EPVAT proof barrel of 600 mm length (m/s)
 Maximum pressure, average, 21±2°C, standard EPVAT proof barrel by CIP (bar)
 ≤3300

 Precision, average mean radius, target at 100 m, standard proof barrel of 600 mm length (mm)

 Penetration of mild steel plate at 400 m from the muzzle of barrel, given by thickness of perforated plate (mm)

Operating temperature (°C)
 Storage temperature (°C)
 54 to +52
 5 to +3

(with daily temperature differences less than 10 °C)

Bullet extraction force, average (N) ≥300

Waterproofness
 Cartridges are waterproof (bubbles test)

 Functioning Cartridges function all specified weapons without casualty at ambient temperatures, at -54°C and +52°C

Shelf life under storage conditions, minimum, years

### **Round elements:**

• Case material Brass 70/30

Bullet jacket material
 Core material
 Primer cup type, model
 Brass 90/10 (gilding metal)
 Steel and lead/antimony alloy
 Boxer type, non-corrosive, ø5.5 LR

## Packaging (suggested, can vary according to the specific requirements):

• Type 10 rounds in small carton box, 90 small carton boxes (900 rounds)

in the M2A1 waterproof metal box, 51 M2A1 metal boxes on the pallet

(45,900 rounds)

• Case/box dimensions (mm) M2A1 metal box: 279.4x141.3x171.5; pallet: 1200x800x670

Case/box gross weight (kg)
 M2A1 metal box: approx. 18.5; pallet: approx. 963

• Case/box volume (dm³) M2A1 metal box: 6.7; pallet: 643



