

9x19 mm, LUGER, FMJ,124 gr

Pistol ammunition

Full metal jacket bullet, lead/antimony core. For law enforcement applications, training and target shooting and range competition. UN transport classification UN0012, 1.4S

 $\begin{array}{lll} \text{Bullet type} & \text{FMJ} \\ \text{Bullet weight (g)} & 8.00 \pm 0.10 \\ \text{Sectional density, lb/in}^2 & 0.141 \\ \text{Jacket} & \text{CuZn 10} \end{array}$

Core Lead/Antimony alloy

Case material CuZn 30 Case length, maximum, mm 19.1

Primer type Boxer type, ø 4.5 SP, non-corosive

Powder charge type spherical double base or flake single base propellant

Powder charge weight (g) 0.30 to 0.34 (depend on propellant type)

Cartridge

Length, maximum, mm 29.7

Round weight, g 12.50 to 12.80 Power factor at 4 inch barrel, qr*ft/s 132 \pm 4

Average velocity at 16 m, 21±2°C, standard NATO EPVAT

proof barrel of 200 mm length (m/s). 340 ± 10

Difference between average velocities (16 m) at

21°C and -54°C or 52°C ≤30

Case mouth pressure (piezo, K6215),

average + 3* standard deviation, standard NATO EPVAT

proof barrel of 200 mm length, $21\pm2^{\circ}$ C (bar) ≤ 2400

Difference between average case maximum mouth

pressure at 21°C and -54°C or 52°C (bar) ≤650

Precision, average mean radius, target at 46 m,

standard NATO precision proof barrel of 200 mm length, (mm) \leq 35 Average standard deviations per X and Y axis, max., (mm) \leq 35

Functioning Cartridges function all specified weapons without

casualty at ambient temperatures, at 21°C, -54°C and +52°C

Bullet extraction force, average (N) min. 250

Waterproofness Cartridges are waterproof (bubbles test)

Operating temperature (°C) -54 to +52Storage temperature (°C) -5 to +30

Shelf life under storage conditions and original

inner package , minimum, years 20

Packaging (can vary according to the specific requirements)

Type 50 rounds in small plastic waterproof box, 20 plastic boxes (1000 rounds) in the

UN certified shipment carton box, 100 shipment carton boxes on the pallet

(100.000 rounds)

Pallet dimensions (mm) shipment carton box: 270x150x190; pallet: 1200x800x1200 Case/box gross weight (kg) shipment carton box: approx. 13.3; pallet: approx. 1344

Case/box volume (dm³) shipment carton box: 7.7; pallet: 1152

